



LDZF 系列

立式 压力蒸汽灭菌器（医疗） 立式 高压蒸汽灭菌器（非医疗）

Vertical Pressure Steam
Sterilizer

新品



型号	LDZF-30KB LDZF-30KB-II LDZF-30KB-III (医疗)	LDZF-30L LDZF-30L-II LDZF-30L-III (非医疗)	LDZF-50KB LDZF-50KB-II LDZF-50KB-III (医疗)	LDZF-50L LDZF-50L-II LDZF-50L-III (非医疗)	LDZF-75KB LDZF-75KB-II LDZF-75KB-III (医疗)	LDZF-75L LDZF-75L-II LDZF-75L-III (非医疗)
容积	30 立升		50 立升		75 立升	

Product Features

产品特点

实行微电脑智能控制系统：采用“LED”数显运行工作循环程序，灭菌结束（报警）后自动停机；

安全联锁装置：采用电子与机械互动的安全控制结构，确保锅内有压力时联锁装置自动锁紧锅盖，避免了误操作或使用不当而产生的不安全因素；

锅盖启闭装置：采用拨杆式 8 柱销同步伸缩结构，使锅盖开启与锁紧安全可靠、灵活轻巧；

预置程序：可预置固定程序针对固体的灭菌；

记忆存储系统：可存储上次灭菌程序，便于二次操作；

校验接口：提供温度、压力检验接口，方便对锅内多点温度进行检测；

操控台动态：数显屏与指示灯可显示设定的灭菌工作动态与运行的功能提示；

安全配置：锁盖联动装置、电控式超温过压保护系统、防干烧保护功能、机械式安全泄压阀、漏电保护装置、自动故障检测系统；

打印功能：实时打印灭菌阶段中的灭菌温度和灭菌时间。

Intelligent microcomputer control system: Using LED digital control system; After sterilization finished, sterilizer will automatic alarm and shut down.

Interlock device: The control system can real time supervision the sterilizer chamber's temperature and pressure. Only under the safety temperature and pressure can open the sterilier's cover.Mack sure the operator's safety.

The structure of cover's opening: Using 8 rotary extendable stick to improve sealing and safety performance.

Preset program: Can preset fixed program that sterilize solid body.

Memory storage system: Store the last operation program so convenient next operation.

Interface check: provide temperature and pressure check interface; convenient to check multiple position temperature measurement.

Digital display screen: Digital display screen and working indicator light display running state.

Safety devices: Interlock device, overtemperature and over pressure protecting system,burned protection, safety relief valve, current leakage protector and automatic fault detection.

Print function: Print the current temperature and sterilization time.

Technical Parameter

技术参数

参数 / 型号 Parameter / Model	LDZF-30KB LDZF-50KB LDZF-75KB (医疗)	LDZF-30L LDZF-50L LDZF-75L (非医疗)	LDZF-30KB-II LDZF-50KB-II LDZF-75KB-II (医疗)	LDZF-30L-II LDZF-50L-II LDZF-75L-II (非医疗)	LDZF-30KB-III LDZF-50KB-III LDZF-75KB-III (医疗)	LDZF-30L-III LDZF-50L-III LDZF-75L-III (非医疗)
配置 Configuration	标准配置 Basic Configuration		自动排气 Auto exhaust		干燥 Drying	
主体材质 The main material	不锈钢 Stainless steel		不锈钢 Stainless steel		不锈钢 Stainless steel	
容积 / 毛 重 Volume / GW	30L /80Kg 50L / 90Kg 75L / 100Kg		30L /80Kg 50L / 90Kg 75L / 100Kg		30L /80Kg 50L / 90Kg 75L / 100Kg	
电压 / 功率 Voltage / Power	220V / 3.5Kw		220V / 3.5Kw		220V / 3.5Kw	
包装尺寸 (长 x 宽 x 高 mm) Packing size (L X W X H mm)	660 X 610 X 970 660 X 610 X 1120 660 X 610 X 1270		660 X 610 X 970 660 X 610 X 1120 660 X 610 X 1270		660 X 610 X 970 660 X 610 X 1120 660 X 610 X 1270	
灭菌室容积 (直径 x 高度 mm) Sterilization chamber volume(D X H mm)	370 X 320 370 X 500 370 X 690		370 X 320 370 X 500 370 X 690		370 X 320 370 X 500 370 X 690	
时间设定范围 Time setting range	0-99 h		0-99 h		0-99 h	
额定工作压力 Rated working pressure	0.217MPa		0.217MPa		0.217MPa	
灭菌温度设定范围 Sterilization temperature setting range	50~134℃		50~134℃		50~134℃	